

# Tacticomp™ 5

Mounted & Dismounted  
Tactical Soldier System

New for 2009



# Tacticomp™ 5

SNC C4N's Tacticomp 5 is a Mounted or Dismounted Mini-Tablet Soldier System. The Tacticomp 5 can be used with other SNC C4N accessories such as the Combat Controller and Tactisight. Powered by an Intel processor with built-in advanced wireless and GPS capabilities, the Tacticomp 5 can handle any Tactical application, from situational awareness with moving maps, video and voice. The Tacticomp 5 possesses a specialized level of integration and ruggedness. Networking the Dismounted Warfighter has never been easier.



Processor:	1.0 GHz Intel® Processor	Optional Accessories:	60 Wh Smart Li-Ion Battery Pack and extra Stylus
O/S:	Windows®	Battery/Run-time:	Extended Life Li-Ion Battery, 3-5 hours of continuous operation with Extended Life Batteries, depending on configuration
Memory:	Up to 1GB DDR SDRAM, user configurable	Case:	Custom Composite/Magnesium Alloy Housing
Graphics:	Intel Graphics Accelerator for image manipulation. OpenGL compliant	LCD Protection:	Hardened Polycarbonate Lens, sealed and isolated from LCD Display for greater protection against debris and high impact
Display:	6.5" XGA (1020 x 768), Color TFT LCD Display, Backlit, Manual Brightness Control, Color Mapping for NVG use.	Seals:	O-ring seals on Case, Lens, Doors and Battery. 3 Fast-access, O-ring sealed Doors
Wireless:	Ad hoc, Spread Spectrum, Self-forming and Self-healing Mesh Network Transceiver. (Optional: 802.11b)	Data Security:	Removable Disk Drive FIPS 140-2 approved 256-bit AES Network Encryption Drivers
USB:	1 - USB 2.0 host ports (480 Mbps)	Connector Protection:	Removable Elastomeric Caps for dust, mud and moisture protection
GPS:	12-channel C/A GPS receiver. Built-in active GPS antenna	Anti-Tamper Design:	Fanless, fully-sealed case design with tamper detection
User Input:	1- High Resolution Inductive Sensor Stylus and 1 spare Stylus, 4 user buttons, 4 directional and 1 "Enter" Buttons, 2- Screen Brightness Buttons, Power On/Off Button	Environmental Specs:	Storage Temperature: -26 to +160° F Operating Temperature: -22 to +160°F Non-operating Humidity Range: 5% to 100% Operating Humidity Range: 5% to 100%.
Power:	60Whr Extended Life Li-Ion Smart Battery Pack. 110/220 VAC Switching Power Supply and Charger	Optional Tactical Modem:	Interfaces with wide range of Military radios via external Tactical Modem
Battery Protection:	Over-charge, over-discharge, over-current, over-temperature protection		
Ethernet:	1-RJ-45 Ethernet Connector. Ethernet connector is fully environmentalized when used with a mating environmental connector for protection against explosive atmospheres, sand, dust and water		

For further inquires, please call 510.446.8400 ext 0

Data contained within this document is subject to change at any time at SNC's discretion.

All rights reserved, 2009. Sierra Nevada Corporation, 444 Salomon Circle Sparks, NV 89434 p: 775.331.0222 f: 775.331.0370