

# SNG<sup>®</sup>

## AN/PYQ-10A (C) SKL v3.1



### Over 295,000 Devices Fielded

The (AN/PYQ-10A (C)) Simple Key Loader (SKL) latest production version is called the SKL V3.1 and offers improved Fill Port ruggedization, enhanced brightness/contrast LCD, and a touchscreen interface that supports both finger and stylus input.

The AN/PYQ-10A (C) SKL v3.1 meets NSA Information Assurance certification security requirements by providing a secure means of distribution and storage of COMSEC material, mission data and configuration files and continues to be compatible with a multitude of cryptographic systems.

# AN/PYQ-10A (C) SKL v3.1

## Simple Key Loader

### Specifications

Processor:	800Mz digital media processor
OS:	Windows Embedded CE 6.0
Memory:	256MB
Storage:	32GB
Display:	3.5" QVGA, 600 cd/m2 brightness, 800:1 contrast ratio, 85°/85°/85°/85° viewing angle
USB:	1 USB mini-A host port & 1 USB mini-B device port
User Interface:	Touchscreen (glove compatible), keypad, Brightness control, power on/off button, recessed "zeroize" button
Power:	Standard battery pack: Waterproof, 25 Whr, Li-Ion battery pack Heavy duty battery: 50 Whr, Li-Ion battery pack
Accessories:	8 AA quick-change, Alkaline battery pack, Battery Charger Kit, Padded carrying case holds SKL spare battery packs & extra stylus
Size/Weight:	7.7" x 4.3" x 2.5", 2.13 lbs. with standard battery
Case:	Composite housing/access port, TPR overmold
Seals:	O-ring seals on case, lens, doors & battery for fast-access, O-ring sealed door



### Specifications

Battery/Continuous Operation:	Standard Li-Ion battery pack: >6 hours Heavy Duty Li-Ion battery pack: >12 hours
LCD Protection:	Glass on film on glass surface, 7H surface hardness, sealed & isolated from LCD for greater protection against high impact
Data Security:	Removable crypto ignition key (CIK)
Connector Protection:	Removable elastomeric cap for dust, mud & moisture protection
Storage Temperature:	-30°C to 71°C, MIL-STD-810G, methods 501.5 & 502.5, procedure I
Operating Temperature:	-30°C to 60°C, MIL-STD-810G, methods 501.5 & 502.5, procedure II
Low Pressure Altitude:	-110 feet to +40,000 feet, MIL-STD-810G, method 500.5, procedure II – operation
Solar Radiation:	MIL-STD-810G, method 505.5, procedures I & II – cycling & steady state
Rain:	MIL-STD-810G, method 506.5 rain, procedure I – rain & blowing rain
Humidity:	95 % ±5 %, based on MIL-STD-810G, method 507.5, procedure II – aggravated cycle
Salt Fog:	MIL-STD-810G, method 509.5 – non-operational



444 Salomon Circle | Sparks, NV 89434 | Phone: (775) 331-0222 | Email: mst@sncorp.com | Website: sncorp.com

DATA CONTAINED WITHIN THIS DOCUMENT ARE SUBJECT TO CHANGE AT ANY TIME AT SNC'S DISCRETION | Sierra Nevada Corporation and SNC are trademarks of Sierra Nevada Corporation | ©2022 Sierra Nevada Corporation  
Warning - Exports, sales, and offerings of the products and technology discussed herein are subject to U.S. Government approval.

9/21/2022